

VLIW Processors

- Very Long Instruction Word
- N-wide VLIW issues packets of N instructions simultaneously. Compiler guarantees independence of those N instructions.

add r5, r4, r1	multd f6, f4, f2	lw r2, 0(r7)	sub r8, r6, r1	beqz r9, label
sub r11, r5, r1	addd f8, f0, f6	sw r5, 8(r7)	nop	beqz r2, l2

Loop Unrolling in VLIW

Memory reference 1	Memory reference 2	FP operation 1	FP op. 2	Int. op/branch	Clock
LD F0,0(R1)	LD F6,-8(R1)				1
LD F10,-16(R1)	LD F14,-24(R1)				2
LD F18,-32(R1)	LD F22,-40(R1)	ADDD F4,F0,F2	ADDD F8,F6,F2		3
LD F26,-48(R1)		ADDD F12,F10,F2	ADDD F16,F14,F2		4
		ADDD F20,F18,F2	ADDD F24,F22,F2		5
SD 0(R1),F4	SD -8(R1),F8	ADDD F28,F26,F2			6
SD -16(R1),F12	SD -24(R1),F16				7
SD -32(R1),F20	SD -40(R1),F24			SUBI R1,R1,#48	8
SD -0(R1),F28				BNEZ R1,LOOP	9

- Unrolled 7 times to avoid delays
- 7 results in 9 clocks, or 1.3 clocks per iteration
- Need more registers in VLIW

Limits to Multi-Issue Machines

- 1 branch in 5 instructions => how to keep a 5-way VLIW busy?
- Latencies of units => many operations must be scheduled
 - Need about Pipeline Depth x No. Functional Units of independent operations to keep machines busy
- Instruction mix may not match hardware mix
 - need duplicate FUs, increased flexibility
- Increase ports to Register File (VLIW example needs 6 read and 3 write for Int. Reg. & 6 read and 4 write for FP reg)
- Increase ports to memory
- Decoding SS and impact on clock rate

Superscalar vs. VLIW

- Superscalar Positives
- VLIW Positives

HW support for More ILP

- *Speculation*: allow an instruction to issue that is dependent on branch predicted to be taken *without* any consequences (including exceptions) if branch is not actually taken (“HW undo”)
- Often combined with dynamic scheduling
- Tomasulo: separate *speculative* bypassing of results from real bypassing of results
 - When instruction no longer speculative, write results (*instruction commit*)
 - execute out-of-order but commit in order

CSE 240

Dean Tullsen

Four Steps of Speculative Tomasulo Algorithm


1. **Issue**—get instruction from FP Op Queue
 - If reservation station and reorder buffer slot free, issue instr & send operands & reorder buffer no. for destination. Operands may be read from register file or reorder buffer.
2. **Execution**—operate on operands (EX)
 - When both operands ready then execute; if not ready, watch CDB for result; when both in reservation station, execute
3. **Write result**—finish execution (WB)
 - Write on Common Data Bus to all awaiting FUs & reorder buffer; mark reservation station available.
4. **Commit**—update register with reorder result
 - When instr. at head of reorder buffer & result present, update register with result (or store to memory) and remove instr from reorder buffer.

CSE 240

Dean Tullsen

Hardware Speculative Execution

- Need HW buffer for results of uncommitted instructions: *reorder buffer*
 - Reorder buffer can be operand source
 - Once operand commits, result is found in register
 - 3 fields: instr. type, destination, value
 - Use reorder buffer number instead of reservation station
 - Instructions commit in order
 - As a result, its easy to undo speculated instructions on mispredicted branches or on exceptions



CSE 240

Dean Tullsen

Reorder buffer execution example

Reservation Stations						
name	busy	op	Vj	Vk	Qj	Qk
int1						
int2						
mult1						
mult2						

Reorder Buffer					
Entry	Busy	Instruction	State	Destination	Value
1					
2					
3					
4					
5					
6					
7					
8					
9					
10					
11					

```
LD  F0, 0(R1)
MULTD F4, F0, F2
SD  0(R1), F4
SUBI R1, R1, #8
BNEZ R1, loop
```

FP Register Status							
	F0	F2	F4	F6	F8	F10	F12 ...
Reorder #							
Busy							

CSE 240

Dean Tullsen

Speculative Execution


- The re-order buffer and in-order commit allow us to flush the speculative instructions from the machine when a misprediction is discovered.
- ROB is another possible source of operands
- ROB can provide precise exceptions in an out-of-order machine
- ROB allows us to ignore exceptions on speculative code.
- Compiler speculation vs. hardware speculation?

CSE 240

Dean Tullsen

Compiler support for ILP: Software Pipelining

- Observation: if iterations from loops are independent, then can get ILP by taking instructions from different iterations
- Software pipelining: reorganizes loops so that each iteration is made from instructions chosen from different iterations of the original loop



CSE 240

Dean Tullsen

SW Pipelining Example

Unrolled 3 times

```

1 LD  F0, 0(R1)
2 ADDD F4, F0, F2
3 SD  0(R1), F4
4 LD  F6, -8(R1)
5 ADDD F8, F6, F2
6 SD  -8(R1), F8
7 LD  F10, -16(R1)
8 ADDD F12, F10, F2
9 SD  -16(R1), F12
10 SUBI R1, R1, #24
11 BNEZ R1, LOOP
    
```

Software Pipelined

```


LD  F0, 0(R1)
ADDD F4, F0, F2
LD  F0, -8(R1)
1 SD  0(R1), F4; Stores M[i]
2 ADDD F4, F0, F2; Adds to M[i-1]
3 LD  F0, -16(R1); loads M[i-2]
4 SUBI R1, R1, #8
5 BNEZ R1, LOOP
SD  0(R1), F4
ADDD F4, F0, F2
SD  -8(R1), F4
    
```

CSE 240

Dean Tullsen

Compiler Support for ILP: Trace Scheduling

- Creates long basic blocks by finding long paths in the code



CSE 240

Dean Tullsen

Trace Scheduling

- Parallelism across IF branches vs. LOOP branches
- Two steps:
 - *Trace Selection*
 - Find likely sequence of basic blocks (*trace*) of (statically predicted) long sequence of straight-line code
 - *Trace Compaction*
 - Squeeze trace into few VLIW instructions
 - Need bookkeeping code in case prediction is wrong

CSE 240

Dean Tullsen

HW support for More ILP

- Avoid branch prediction by turning branches into *conditionally executed instructions*: (aka predicated instructions)
- if (x) then A = B op C else NOP
- If false, then neither store result or cause exception
 - Expanded ISA of Alpha, MIPS, PowerPC, SPARC have conditional move; PA-RISC can annul any following instr, IA64 can predicate any instruction (even have multiple predicates)

```
ld    F2, 0(R2)
addd  F4, F2, F0
multd F6, F4, F4
beqz  R3, go_on
addd  F10, F0, F8
addi  R2, R2, #8
go_on: addi  R2, R2, #8
bnez  F6, loop
```

CSE 240

Dean Tullsen

Predicated Execution

- Drawbacks to conditional instructions
 - Still takes a clock & alu even if “annulled”
 - Stall if condition evaluated late
 - Complex conditions reduce effectiveness; condition becomes known late in pipeline
 - requires more operands! Typically only available as *conditional move*.
- Advantages
 - eliminate prediction, misprediction
 - longer basic blocks, ...

CSE 240

Dean Tullsen

ILP in real code




FIGURE 4.40 The effect of window size shown by each application by plotting the average number of instruction issues per clock cycle.

- Based on all kinds of ideal assumptions. Further limited by:
 - realistic branch prediction
 - finite renaming registers
 - imperfect alias analysis for memory operations

CSE 240

Dean Tullsen


PowerPC 620

- speculative, out-of-order, superscalar processor
- fetches 4, issues 4, completes 4, 6 independent functional units
- Reservation stations, reorder buffer, register renaming in the register file

CSE 240

Dean Tullsen


PowerPC 620



CSE 240

Dean Tullsen

PowerPC 620 Pipeline Structure



- Fetch
- Decode
- Issue
- Execute
- Commit

CSE 240

Dean Tullsen

PowerPC 620 Performance




FIGURE 4.52 The average number of instructions that the fetch unit can provide to the issue unit varies between 3.2 and 4, with an average of 3.4 for the integer benchmarks and 3.8 for the FP benchmarks.

CSE 240

Dean Tullsen

PowerPC 620 Performance




FIGURE 4.57 The breakdown of the ideal IPC of 4.0 into its components.

ILP Summary

- Parallelism is absolutely critical to modern computer system performance, but at a very fine level.
- Mechanisms that create, or expose parallelism: loop unrolling, software pipelining, code motion
- Mechanisms that allow the machine to exploit ILP: pipelining, superscalar, dynamic scheduling, speculative execution