

CSE 101 Calibration Homework
Background, (Order and Recurrence Relations, simple algorithms), MergeSort
Due October 3
100 points total, DOES NOT COUNT TOWARDS GRADE

Is $4^{\lceil \log n \rceil} \in O(n^2)$? Why or why not? (When unspecified, logs are base 2). Is $\log(n!) \in \Omega(n \log n)$? Why or why not? Is $4^n \in O(2^n)$? Why or why not? Is $n + (n - 1) + (n - 2) + \dots + 1 \in O(n)$? Why or why not? (5 points each.)

Page 496-501 of text; 10 pts.each 1e, 6

Triangles(20 points) Let G be an undirected graph with nodes $v_1, \dots, v_n$. The *adjacency matrix* representation for G is the $n \times n$ matrix M given by: $M_{i,j} = 1$ if there is an edge from v_i to v_j , and $M_{i,j} = 0$. A *triangle* is a set $\{v_i, v_j, v_k\}$ of 3 distinct vertices so that there is an edge from v_i to v_j , another from v_j to v_k and a third from v_k to v_i . Give and analyze an algorithm for counting the number of triangles in a graph G , given by its adjacency matrix representation. Analyze your algorithm's worst-case performance first in terms of just the number of nodes n of the graph, then in terms of n and the number of edges m of the graph. Your algorithm should be faster when $m \ll n^2$.

Summing triples (20 points) Let $A[1, \dots, n]$ be an array of positive integers. A *summing triple* in A is 3 distinct indices $1 \leq i, j, k \leq n$ so that $A[i] + A[j] = A[k]$. Give and analyze an algorithm that, given A , determines whether there is any summing triple in A . Try to be better than $O(n^3)$.

Implementation (20 points) Implement the algorithm you gave for the summing triples problem above. Try it on random arrays where each element $A[i]$ is chosen in the range $1 \dots n$, for $n = 2^6, 2^8, 2^{10}, 2^{12}, 2^{14}, 2^{16}, 2^{18}$ and 2^{20} . Plot its performance on a $\log_2 n$ vs. $\log_2$ of the time scale. Then try the same experiment on random arrays where each element is chosen in the range $1, \dots, n^2$. Do you see a difference? If so, can you explain it?